

Description

Crest Defoamer-S is a one layer light tan liquid that is water soluble. The product was developed to reduce excessive foaming in rinse tanks in an iron phosphate line. Also, the product is used in waste treatment plants to reduce foaming when chemicals are introduced to the waste treatment and the waste treatment tanks start to foam. Crest Defoamer-S may be used in air agitated dip tanks or spray washer that are using alkaline products to clean.

- » Supplied in a liquid form that easily dissolves in water solutions.
- » Used at very low concentrations and therefore economical to use.
- » Flash point above 245°F.

Method of Use

Application Methods

- » Add into foaming tanks.

Mixing Instructions

1. Dilute Defoamer-S with equal parts water.
2. Add 1 to 2 oz. of the diluted mixture to 50 to 100 gallons of the solution that is foaming.
 - » Each situation is different, therefore, testing should be done by the operator to determine the optimum amount of Defoamer-S.

Caution

Refer to product labels and Safety Data Sheets for precautionary and handling information.

Warranty and Liability Disclaimer

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience; however, since conditions of actual use are beyond our control, any recommendations, or suggestions, are made without warranty, expressed or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.